



**FLUID HANDLING
IN EVERY DIRECTION**

Chemical stor® - CS2

Backed by our 20 year structural guarantee*

The base is manufactured from 3mm mild steel sheet with pressed ribs. All the corner posts, main rails and cross members are from rolled hollow section. The roof is pressed as required with suitable bracing and fully welded around the perimeter, while the back, side and door panels are pressed from 2mm mild steel sheet and corrugated where required. The bulkhead door is 1250mm wide and fitted with a single cam door gear which is secured with a padlock (not supplied). Inside the unit there are shelving units either side of the door, the fully seam welded sump is fitted with a removable galvanised grid mesh deck and high and low level louvre vents complete with flame arrestor mesh are fitted as standard. The unit is shot blasted before being painted.

*Details available on request



Size	3000mm L x 2440mm W x 2600mm H
N° of containers	72x 25ltr including the deck area under the shelves
Sump capacity	1098ltr
Colour	Green RAL 6029
Tare weight	1582kg

Note: This unit will be delivered by an articulated vehicle, therefore please ensure that a vehicle of this size can access your premises before ordering and advise us accordingly.

This model has more usable deck space between the 2 sets of shelves than model CS1

D&H Group. Maple House, Hamlin Way, Kings Lynn. Norfolk. PE30 4NG.
Tel: (01553) 819590. Fax: 0645 270 3334. Email: info@dandhgroup.co.uk