



**FLUID HANDLING  
IN EVERY DIRECTION**

### **Chemical stor® - CS3**

The base is manufactured from 3mm mild steel sheet with RHS cross members, all the corner posts, main rails and cross members are from rolled hollow section and the back side and door panels are pressed from 2mm mild steel sheet corrugated where required. The roof is pressed and fitted with suitable bracing and fully welded around the perimeter. High and low level louvre vents complete with flame arrestor mesh are fitted as standard and the double steel sliding doors run on easy glide tracks. The unit uses grid mesh above the fully seam welded sump, has a full width/full depth shelf and two full width 700mm deep shelves above that. The unit is shot blasted before being painted.



<b>Size</b>	3000mm L x 1500mm W x 2450mm H
<b>N° of containers</b>	80 x 25ltr + smaller containers up to 5ltr
<b>Sump capacity</b>	1125ltr
<b>Colour</b>	Green RAL 6029
<b>Tare weight</b>	1048kg

Note: This unit will be delivered by an articulated vehicle, therefore please ensure that a vehicle of this size can access your premises before ordering and advise us accordingly.

**D&H Group.** Maple House, Hamlin Way, Kings Lynn. Norfolk. PE30 4NG.  
Tel: (01553) 819590. Fax: 0645 270 3334. Email: [info@dandhgroup.co.uk](mailto:info@dandhgroup.co.uk)