

ACS drinking water range

WARRANTY
TANK
100%
10 years

WATER STORAGE


Supplying drinking water is a vital necessity and usually a heavy investment.

Our flexible tanks offer a less expensive solution, just as safe and very easy to install. The fabric and accessories are ACS certified to guarantee the safety of materials in contact with water intended for human consumption.

Several applications are possible:

- Supplying the military and security troops,
- Supplying building site workers,
- Temporary storage during maintenance work on an existing network,
- Permanent storage for isolated dwellings,
- Water storage in spas.

SKELETON DIAGRAM



TECHNICAL FABRIC

- ACS range: high resistance woven 100% polyester with PVC coating (950 g/m² minimum – beige/white).
- Double sided UV stabilised
- Tear strength: 550 N minimum
- Tensile strength: 400 DaN / 5 cm minimum

STANDARD ACCESSORIES

E11-ACS01 :

- No. 1: 4" polyamide vent with cap
- No. 2: DN 50 polyamide tapping + ¼ turn ACS valve
- + DN 50 stainless steel symmetrical connection
- Consolidated corners with protection plates
- Repair kit & Leaflet

EUROPEAN REGULATION

Complies with EC Directives 2002/72, 97/48, 85/572.

HOMOLOGATION / CERTIFICATION

Health Safety Certification (ACS) delivered by the Lyon Health Safety and Environment Laboratory

WARRANTY

- 100% 10-year manufacturer warranty for fabric and manufacturing for the drinking water application.
- Please inquire for further details.



5 m³ with Army camouflage



Did you know?

Our drinking water tanks have been analysed and monitored by the DDASS for 5 years: water quality complies!



MAIN ADVANTAGES FOR THIS APPLICATION

The flexible tank allows you to protect water from air, light and any contamination. The water remains intact...
Safe drinking!

TANK DIMENSIONS AND CAPACITIES ACS

Part number	Volume in m ³	Empty dimensions in m	Max height in m	Empty weight in kg
005000-ZCC1F	5	3,90 x 2,56	0,90	20
010000-ZCC1F	10	4,25 x 3,84	1,10	33
015000-ZCC1F	15	5,60 x 3,84	1,20	43
020000-ZCC1F	20	7,05 x 3,84	1,30	54
030000-ZCC1F	30	7,25 x 5,12	1,30	74
050000-ZCC1F	50	10,70 x 5,12	1,30	108
080000-ZCC1F	80	9,90 x 7,68	1,60	150
100000-ZCC1F	100	10,30 x 8,96	1,60	184