

Tel: 01553 819590

2 YEAR WARRANTY



2 YEAR WARRANTY



EN 12566-Pt 3.
Certified 96.2% average efficiency

Efficient, reliable, sewage treatment systems for all residential, commercial and Industrial applications





For any application, residential, commercial, industrial, where there is no access to a mains sewer, the **MATRIX** sewage treatment plant provides an extremely efficient, reliable and cost effective solution to sewage disposal. The **MATRIX** system is a single tank unit up to 300 residential population equivalent and a modular system for larger applications.

Performance with Peace Of Mind

Recent changes in regulations mean that **ONLY** fully CE marked and certified treatment plants are acceptable for installation to comply with legislation. The **MATRIX** treatment plant has undergone extensive independent testing in accordance with EN12566-3 making it fully compliant with the new European Standard. It is important to note that the new standard relates to **ALL** units in the range from 6 person (residential equivalent) to 50 person (residential equivalent) and to qualify for CE marking must include for both process and structural testing, including installation in groundwater conditions. Unlike many manufacturers, C & L Fabrication Ltd have had all **MATRIX** treatment plants in the range to 50pe fully tested in all aspects of EN12566-3 with the achievement of market leading results and as such is fully CE compliant.

The **MATRIX** sewage treatment system is designed to achieve the minimum required effluent quality standard of 20mg/litre Biochemical Oxygen Demand (BOD) : 30mg/litre Suspended Solids (SS) : 20mg/litre Ammoniacal Nitrogen (NH₄), which in European Standard performance testing relates to an efficiency of better than 94%, the certified performance of the **MATRIX** system is that it produces an average final effluent quality of 11mg/litre Biochemical Oxygen Demand (BOD) : 16mg/litre Suspended Solids (SS) and 7mg/litre Ammoniacal Nitrogen. This relates to an average efficiency ratio of 96.2%, better than most other manufacturers, with individual test efficiency results being as high as 98.8%. As part of the test procedure the **MATRIX** system was proven to have one of the lowest operating costs.

Process

The **MATRIX** treatment system is a three stage biological process contained within a single tank structure, based on the principles of a submerged bed reactor and designed in accordance with the requirements of BS6297. Careful configuration of the internal flowpath and the inclusion of non-mechanical recirculation systems ensures optimal process performance as demonstrated by the exceptional results obtained from the independent testing, providing complete peace of mind for the end user. There are **NO** electrical or mechanical components within the treatment plant thereby eliminating the need for any specialist servicing arrangements ensuring that any maintenance requirements on the **MATRIX** system are kept to an absolute minimum.



CLF1 - 6pe Fully Installed.



CLF1 - 6pe Treatment Plant ready for delivery.



CLF9 - 70pe Treatment Plant being Loaded.

Servicing & Maintenance

The **MATRIX** system has minimal mechanical components and therefore requires only simple maintenance procedures ensuring that, whether it is a 6 person unit or a 300 person unit, annual maintenance costs remain the least of your worries.



TECHNICAL DATA

Model Ref	PE	BOD/day Kg	Flow/day m3	Length mm	Width mm	Depth mm	Inlet Size mm	Weight kg	Blower Rating
CLF 1	6	0.36	1.20	1500 diameter		2118	160	200	60W
CLF 1A	9	0.54	1.80	1700 diameter		2118	160	250	60W
CLF2	12	0.72	2.40	1900 diameter		2118	160	300	80W
CLF3	18	1.08	3.60	2500 diameter		2174	160	600	120W
CLF4	25	1.50	5.00	4710	1600	2174	160	1200	120kW
CLF5	30	1.80	6.00	4010	2124	2174	160	1400	0.37kW
CLF6	40	2.40	8.00	5060	2124	2174	160	1700	0.37kW
CLF 7	50	3.00	10.00	5610	2124	2174	160	1900	0.37kW
CLF 8	60	3.60	12.00	6010	2124	2174	160	2100	0.75kW
CLF 9	70	4.20	14.00	6810	2124	2174	160	2200	0.75kW
CLF 10	80	4.80	16.00	6760	2524	2174	160	2400	0.75kW
CLF 11	90	5.40	18.00	7360	2524	2174	160	2650	0.75kW
CLF 12	100	6.00	20.00	7760	2524	2174	160	2900	0.75kW
CLF 13	125	7.50	25.00	9100	2524	2174	160	3100	0.75kW
CLF 14	150	9.00	30.00	10600	2524	2174	160	3300	1.10kW
CLF 15	200	12.00	40.00	12000	2524	2174	160	3500	1.10kW
CLF 16	250	15.00	50.00	12000	2524	2674	160	3700	1.10kW
CLF 17	300	18.00	60.00	12000	2524	2712	160	4000	2.00kW

MATRIX Benefits

- Free nationwide site surveys and technical proposal with no obligation.
- Full technical back up and customer service support.
- Free consent to discharge applications. (statutory fees only).
- Nationwide network of service engineers
- Supply only or full supply and installation through certified installers.
- Single tank installation to minimize costs
- Failure alarm systems as standard, not at additional cost
- GSM telemetry dial out alarm units available at small additional cost
- No mechanical or electrical parts within the unit.
- Robust Polypropylene construction for easy and cost effective installation
- No visual intrusion. Flat, flush ground level covers suitable for 1 tonne load.
- Simple installation in vehicular areas, up to D400 loading.
- Low running and maintenance costs
- Integral discharge pumps where required (all models) no additional tanks.
- Deep inlet inverts available to avoid pumping crude sewage to plant.

Direct Dial Sales & Technical helpline : 01553 819590

Tel: 01553 819590



Specialists in Plastic Fabrication

Other products include:

***Pumping Stations, Grease Traps, Kiosk & Housings,
Storage Tanks and Bespoke fabrications -
if you can draw it, we can build it!***

T: 01553 819590

F: 0845 270 3334

Email: info@dandhgroup.co.uk

Web: www.dandhgroup.co.uk

Maple House

Hamlin Way

Kings Lynn.

Norfolk.

PE30 4NG

Your local distributor is :-

